

MOVING MORE

AN OVERVIEW
OF SANY
CONSTRUCTION
MACHINERY



SANY

Quality Changes the World



SANY SERVICES – YOU CAN RELY ON

FLEXIBLE, FAST AND ALWAYS CLOSE BY –
THAT IS OUR PERFORMANCE PROMISE

Working with our network of dealer partners across the UK and Ireland, we provide industry leading service and support that includes rapid assistance, tailored advice and a reliable supply of SANY genuine parts - that is what we mean by a premium service.



FINANCING AND INSURANCE

SANY offers comprehensive services in close cooperation with SANY Finance to supply a preferred finance solution to our customers.



PARTS SUPPLY

Our dedicated parts warehouse in Glasgow has over 10,000 part lines in stock for our UK & Ireland dealers and customers. Parts are delivered daily to our dealer network to ensure quick response times and to make sure SANY machines are kept running at all times.



SANY GENUINE PARTS

SANY original spare parts guarantee the highest quality and performance for your SANY machine. They also ensure optimum safety for the operator on site and reduce unplanned maintenance and downtime.



MAINTENANCE AND SUPPORT

Our team of UK specialists work closely with our nationwide dealer network to ensure we offer a complete level of support.



TRAINING

SANY has a robust network of certified technicians throughout the UK who are fully trained on SANY equipment and can provide hands-on, field-ready support and technical expertise when you need it, to ensure any downtime is kept to a minimum.



DOCUMENTATION

Handbooks as well as comprehensive documentation for maintenance and operation are available for all SANY machines.

SANY KEY CHARACTERISTICS

QUALITY AND DURABILITY

Innovative design and advanced manufacturing techniques ensure SANY machines deliver incredible durability, reliability and dependable uptime on the toughest construction projects.

PUTTING SAFETY FIRST

We have built a comprehensive safety package into our machines, including camera's, driving alarm, rotating beacon, boom safety valve, overload warning, emergency stop button and battery isolation switch.

BUILT FROM THE BEST

SANY uses only the highest quality components, sourced from world-leading brands you know and trust. Rexroth pumps and valves hum in harmony with Dana transmissions and Cummins engines. Everything is built to deliver power, performance and reliability.

COMFORT AND EASE OF USE

Operators can look forward to maximum comfort and easier operation. From the easy entry and the responsive and precise controls to the ergonomic and comfortable operators seat, everything has been designed to simply get on with working.

COST OF OWNERSHIP

SANY excavators are designed to deliver a lower cost of ownership with features such as steel bodywork for maximum strength and durability, reduced fuel consumption in compliance with Stage V emission standards, extended service levels and uncomplicated maintenance.





MINI EXCAVATORS

COMPACT EXCAVATOR SY10U



- + Powerful Stage V Kubota engine and load sensing auxiliary hydraulics
- + Zero tail swing design
- + Expanding undercarriage (745/1100mm) and adjustable dozer blade
- + Proportional controls and auto QH pipework
- + EVI hydraulics
- + 5 year/500 hours warranty

Operating weight	1195 kg
Rated power	8.8 kW / 2200 rpm
Max. digging depth	1868 mm
Max. dumping height	2096 mm
Tail swing radius	550 mm
Length	3018 mm
Width	745 / 1100 mm
Height	2290 mm



SCAN FOR MORE

MINI EXCAVATORS SY16C | SY18C



- Stage V Yanmar engine and load sensing twin auxiliary hydraulics
- 2-speed tracking
- Proportional controls and auto QH pipework
- Expanding undercarriage (980/1350mm)
- Cab or canopy option
- EVI telematics
- 5 year/5000 hours warranty

Operating weight	1865 kg / 1910 - 1980 kg
Rated power	14.6 kW / 2400 rpm
Max. digging depth	2360 mm
Max. dumping height	2635 mm
Tail swing radius	920 mm
Length	3665 mm
Width	980/1350 mm
Height	2410 mm



SCAN FOR MORE

MINI EXCAVATORS SY18U



- Zero tail swing facilitating work in compact spaces
- Stage V Yanmar and efficient twin auxiliary hydraulics
- Expanding undercarriage (980/1350mm)
- 2-speed tracking
- Easilyrowable with secure tie down points
- EVI telematics
- 5 year/5000 hours warranty

Operating weight	1925 kg
Rated power	14.6 kW / 2400 rpm
Max. digging depth	2360 mm
Max. dumping height	2635 mm
Tail swing radius	920 mm
Length	3515 mm
Width	980/1350 mm
Height	2370 mm



SCAN FOR MORE

COMPACT EXCAVATOR SY20C



Operating weight	1975 kg
Rated power	14.6 kW / 2400 rpm
Max. digging depth	2585 mm
Max. dumping height	2475 mm
Tail swing radius	905 mm
Length	3695 mm
Width	1040 / 1350 mm
Height	2430 mm



SCAN FOR MORE

MINI EXCAVATORS SY19E



Operating weight	1965 kg
Rated power	15 kW / 2000 rpm
Max. digging depth	2360 mm
Max. dumping height	2635 mm
Tail swing radius	900 mm
Length	3624 mm
Width	980 / 1350 mm
Height	2440 mm



SCAN FOR MORE

MINI EXCAVATORS SY26C



- + Short tail swing excavator
- + Stage V Yanmar engine
- + Load-sensing twin auxiliary hydraulics
- + Proportional controls and auto QH pipework

Operating weight	2775 kg
Rated power	14.6 kW / 2400 rpm
Max. digging depth	2810 mm
Max. dumping height	3130 mm
Tail swing radius	915 mm
Length	4160 mm
Width	1550 mm
Height	2410 mm



SCAN FOR MORE



MINI EXCAVATORS SY35U



Operating weight	3860 kg
Rated power	18.2 kW / 2200 rpm
Max. digging depth	3105 mm
Max. dumping height	3460 mm
Tail swing radius	860 mm
Length	4915 mm
Width	1720 mm
Height	2515 mm

- + Lightweight, zero tail swing excavator facilitating work in compact spaces
- + Stage V Yanmar engine
- + Efficient, load-sensing twin auxiliary hydraulics
- + Proportional controls and auto QH pipework
- + EVI telematics
- + 5 year/5000 hours warranty



SCAN FOR MORE



MINI EXCAVATORS SY35E



- + Fully electric with zero emissions
- + Lithium Iron Phosphate (cobalt free) battery
- + Fully flexible, automotive standard charging socket with 3 charging options
- + Long life battery (up to 3,500 full charge cycles)

Operating weight	1965 kg
Rated power	15 kW / 2000 rpm
Max. digging depth	2360 mm
Max. dumping height	2635 mm
Tail swing radius	900 mm
Length	3624 mm
Width	980 / 1350 mm
Height	2440 mm



SCAN FOR MORE

MINI EXCAVATORS SY50U



- + Up to 6 hours run time off a single charge (dependant on application and temperature conditions)
- + Expanding undercarriage (980/1350mm)
- + EVI telematics
- + 5 year/5000 hours warranty

Operating weight	5300 kg
Rated power	29.1 kW / 2400 rpm
Max. digging depth	3420 mm
Max. dumping height	3805 mm
Tail swing radius	980 mm
Length	5390 mm
Width	1960 mm
Height	2630 mm



SCAN FOR MORE

COMPACT EXCAVATOR SY60U



- + Stage V Yanmar engine and load sensing twin auxiliary hydraulics
- + Reduced tail swing excavator with swing boom functionality
- + Compact design for easy manoeuvrability
- + Superb visibility
- + EVI telematics
- + 5 year/5000 hours warranty

Operating weight	6300 kg
Rated power	42.4 kW / 2000 rpm
Max. digging depth	3990 mm
Max. dumping height	3970 mm
Tail swing radius	1350 mm
Length	5830 mm
Width	2000 mm
Height	2530 mm



SCAN FOR MORE

MINI EXCAVATORS SY60C



- + Compact conventional tail-swing excavator
- + Stage V Yanmar engine
- + Load-sensing twin auxiliary hydraulics
- + Swing boom functionality
- + Proportional controls and auto QH pipework
- + EVI telematics
- + 5 year/5000 hours warranty

Operating weight	6 100 kg
Rated power	42.4 kW
Max. digging depth	3950 mm
Max. dumping height	4060 mm
Tail swing radius	1640 mm
Length	6015 mm
Width	2005 mm
Height	1320 mm



SCAN FOR MORE

COMPACT EXCAVATORS



COMPACT EXCAVATOR SY75C



- + Compact design for easy manoeuvrability
- + Stage V Yanmar engine and efficient twin auxiliary hydraulic system
- + Proportional controls and auto QH pipework

- + Extensive programming options
- + EVI technologies
- + 5 year/500 hours warranty



SCAN FOR MORE

COMPACT EXCAVATOR SY80U



- + Extremely compact short-tail-swing excavator
- + Stage V Yanmar engine and powerful twin auxiliary hydraulics
- + Proportional controls and auto QH pipework

Operating weight	8800 kg
Rated power	53.7 kW / 2100 rpm
Max. digging depth	4535 mm
Max. dumping height	5430 mm
Tail swing radius	1480 mm
Length	6500 mm
Width	2220 mm
Height	2550 mm



SCAN FOR MORE

COMPACT EXCAVATOR SY135C



- + Versatile machine with large working radius
- + Stage V Isuzu engine and efficient twin auxiliary hydraulics
- + Proportional controls and auto QH pipework

Operating weight	14666 kg
Rated power	78.5 kW / 2000 rpm
Max. digging depth	5970 mm
Max. dumping height	6630 mm
Tail swing radius	2205 mm
Length	7500 mm
Width	2590 mm
Height	2820 mm



SCAN FOR MORE

COMPACT EXCAVATOR SY155U



Operating weight	16170 kg
Rated power	78.5 kW / 1900 rpm
Max. digging depth	6020 mm
Max. dumping height	7200 mm
Tail swing radius	1500 mm
Length	8015 mm
Width	2590 mm
Height	2820 mm

- + Compact, short-tail-swing excavator
- + Stage V Isuzu engine and powerful twin auxiliary hydraulics
- + Proportional controls and auto QH pipework

- + Air suspension seat, climate control and radio
- + Optional two piece boom available
- + EVI telematics
- + 5 year/5000 hours warranty



SCAN FOR MORE





WHEELED EXCAVATORS

WHEELED EXCAVATOR **SY155W**



- ✚ Compact, wheeled excavator
- ✚ Stage V Deutz engine and twin auxiliary hydraulics
- ✚ Front dozer blade and rear stabilisers
- ✚ TAB boom as standard
- ✚ Air suspension seat, climate control and radio
- ✚ EVI tethers
- ✚ 5 year/5000 hours warranty

Operating weight	15000 kg
Rated power	115 kW / 2000 rpm
Max. digging depth	5400 mm
Max. dumping height	7200 mm
Tail swing radius	2030 mm
Length	8200 mm
Width	2550 mm
Height	3200 / 3996 mm



SCAN FOR MORE

CRAWLER EXCAVATORS



CRAWLER EXCAVATOR **SY215C**



Operating weight	24000 kg
Rated power	129 kW / 2200 rpm
Max. digging depth	6450 mm
Max. dumping height	6735 mm
Tail swing radius	2950 mm
Length	9635 mm
Width	3080 mm
Height	3370 mm

- Powerful excavator with heavy-duty undercarriage
- Stage V Cummins engine and twin auxiliary hydraulic system
- Boxing ring
- Optional long reach boom available
- EVI technologies
- 5 year/500 hours warranty
- Full demolition specification available



SCAN FOR MORE

CRAWLER EXCAVATOR SY215E



- + Fully electric with zero emissions
- + Lithium Ion Phosphate (cobalt free) battery
- + Fully flexible, automotive standard CCS2 DC charging as standard (DC fast charge 1.5 hours)

Operating weight	23200 kg
Rated power	150 kW / 1800 rpm
Max. digging depth	6255 mm
Max. dumping height	6730 mm
Tail swing radius	3125 mm
Length	9910 mm
Width	2980 mm
Height	3440 mm



CRAWLER EXCAVATOR SY265C




- + Up to 8 hours run time off a single charge (dependant on application and temperature conditions)
- + EVI telematics
- + 5 year/5000 hours warranty

Operating weight	27000 kg
Rated power	145 kW / 2000 rpm
Max. digging depth	6705 mm
Max. dumping height	6715 mm
Tail swing radius	3105 mm
Length	10290 mm
Width	3290 mm
Height	3225 mm




CRAWLER EXCAVATOR SY305C



- + Powerful 32-tonne excavator with heavy-duty undercarriage
- + Stage V Cummins engine and twin auxiliary hydraulics
- + Boxing ring

Operating weight	32265 kg
Rated power	209 kW / 2100 rpm
Max. digging depth	6815 mm
Max. dumping height	7359 mm
Tail swing radius	2590 mm
Length	10667 mm
Width	2990 / 3190 mm
Height	3280 mm



SCAN FOR MORE

CRAWLER EXCAVATOR SY390H



- + 40-tonne excavator for heavy-duty applications
- + Stage V Cummins engine and twin auxiliary hydraulic system
- + Heated air suspension seat, climate control and radio/MP3 Player

Operating weight	40000 kg
Rated power	252 kW / 2100 rpm
Max. digging depth	7125 mm
Max. dumping height	7490 mm
Tail swing radius	3550 mm
Length	11430 mm
Width	3190 mm
Height	3780 mm




SCAN FOR MORE

CRAWLER EXCAVATOR SY500H



- + Powerful 52-tonne excavator for heavy-duty applications
- + Stage V Cummins engine and twin auxiliary hydraulics
- + Heated air suspension seat, climate control and radio/MP3 Player

Operating weight	53300 kg
Rated power	298 kW / 2100 rpm
Max. digging depth	7705 mm
Max. dumping height	7650 mm
Tail swing radius	3740 mm
Length	12100 mm
Width	3700 mm
Height	3600 mm



SCAN FOR MORE

CRAWLER EXCAVATOR SY750H



- + Powerful 78-tonne excavator for heavy-duty applications
- + Stage V Cummins engine
- + Powerful, twin auxiliary hydraulics
- + Proportional controls and auto QH pipework

Operating weight	78500 kg
Rated power	391 kW
Max. digging depth	7580 mm
Max. dumping height	7170 mm
Tail swing radius	5390 mm
Length	12879 mm
Width	3499 mm
Height	4981 mm



SCAN FOR MORE



DEMOLITION EXCAVATOR



DEMOLITION EXCAVATOR
SY500HRD

- + Wide, hydraulic telescopic chassis
- + Increased operating range with long 28m boom
- + Stage V Cummins engine
- + Smart hydraulic control system
- + EVI electronics
- + 5 year/500 hours warranty

Operating weight	64 000 kg
Rated power	298 kW / 2100 rpm
Length	20 000 mm
Width	3 400 mm
Height	3 600 mm

SCAN FOR MORE



TELEHANDLERS



TELEHANDLER STH625



- + Turning radius of 3.35m and 3 steer modes
- + Dana hydrostatic transmission for application efficiency
- + Auxiliary venting for fast attachment changing
- + Proportional joystick with auto rpm
- + Comprehensive safety package as standard, including seat belt green beacon
- + EVI electronics
- + 3 year/300 hours warranty with 500hr service intervals

Operating weight	5200 kg
Driving and hydraulic power	55.4 kW
Max. lift height	6000 mm
Max. lift capacity	2500 kg
Max. lift capacity at max. height	2500 kg
Length	4000 mm
Width	1850 mm
Height	1920 mm




SCAN FOR MORE

TELEHANDLER STH625E



- + Fully electric with zero emissions and a travel speed of 20kph
- + 34 kWh LFP battery with up to 8 hours running time
- + Compact design (under 2m height/ width) perfect for urban sites
- + Premium portable charging with 4 charging options (inc AC fast charge)

Operating weight	5100 kg
Driving and hydraulic power	32 kW
Max. lift height	6000 mm
Max. lift capacity	2500 kg
Max. lift capacity at max. height	2000 kg
Length	4000 mm
Width	1850 mm
Height	1920 mm



SCAN FOR MORE

TELEHANDLER STH742



- + Turning radius of 3.85m and 3 steer modes
- + Dana hydrostatic transmission for application efficiency
- + Auxiliary venting for fast attachment changing
- + Proportional joystick with auto rpm

Operating weight	8325 kg
Rated power	55 kW / 2600 rpm
Max. lift height	7 m
Max. lift capacity	4200 kg
Max. lift capacity at max. height	2500 kg
Length	4990 mm
Width	2350 mm
Height	2540 mm



SCAN FOR MORE

TELEHANDLER STH936



- Three selectable steering modes (4WS, 2WS and Crab)
- Precise weight management system
- Cabin comfort with A/C, radio and bluetooth, 10" touchscreen with encoder and 7 LED worklights

Operating weight	9100 kg
Driving and hydraulic power	55 kW
Max. lift height	9600 mm
Max. lift capacity	3600 kg
Max. lift capacity at max. height	1000 kg
Length	4990 mm
Width	2350 mm
Height	2540 mm



SCAN FOR MORE

TELEHANDLER STH1440



- ROPS/FOPS cab offering maximum protection and comfort
- Comprehensive safety package as standard including reversing camera
- EVI telematics for easy fleet management
- 3 year/3000 hour warranty

Operating weight	10980 kg
Rated power	55 kW / 2600 rpm
Max. lift height	14 m
Max. lift capacity	4000 kg
Max. lift capacity at max. height	3000 kg
Length	6160 mm
Width	2420 mm
Height	2595 mm



SCAN FOR MORE

TELEHANDLER STH1840



- + Three selectable steering modes (4WS, 2WS and Crab)
- + Dana hydrostatic transmission for application efficiency
- + Reversing camera & distance sensor as standard
- + Precise weight management system

Operating weight (with forks)	12300 kg
Rated power	55 kW / 2600 rpm
Max. lift height	18 m
Max. lift capacity	4000 kg
Max. lift capacity at max. height	2500 kg
Length	6160 mm
Width	2420 mm
Height	2595 mm



SCAN FOR MORE



WHEEL LOADERS



WHEEL LOADER **SW305**

- Versatile machine for construction, landscaping, horticulture and demolition
- Stage V Deutz, six-cylinder engine
- Efficient load sensing hydraulics
- Spacious ROPS/FOPS certified cab
- EVI technologies
- 5 year/500 hours warranty



Operating weight	14500 kg
Rated power	129 kW / 2200 rpm
Full load bucket capacity	2.3 m ³
Max. dumping height	2689 mm
Full turn tipping load	7714 kg
Length	7518 mm
Width	2545 mm
Height	3405 mm



SCAN FOR MORE

WHEEL LOADER SW405



Operating weight 18500 kg

Rated power 170 kW / 2300 rpm

Full load bucket capacity 3.2 m³

Max. dumping height 5415 mm

Full turn tipping load 13100 kg

Length 8180 mm

Width 3015 mm

Height 3580 mm

- Versatile machine for construction, landscaping, horticulture and demolition
- Stage V Deutz, seven-cylinder engine
- Efficient load sensing hydraulics

- Spacious ROPS/FOPS certified cab
- EVI telematics
- 5 year/5000 hours warranty



SCAN FOR MORE



WE'VE GOT YOU COVERED

SANY has earned a reputation worldwide for reliability, durability and performance but to provide peace of mind and to ensure maximum uptime most SANY machines are backed by the SANY industry leading 5 year warranty*.

That's our commitment to keeping your fleet running at peak performance. It secures your investment for the future and means that if any issues arise with your equipment, you're covered from day one.



* Terms and conditions apply. Check with your local dealer for more information.



FLEXIBLE, FAST AND ALWAYS THERE FOR YOU

THE ADDED BENEFITS SANY OFFERS YOU

We would be happy to advise you, offer financing options and, naturally, take care of maintenance and service.



www.sanyuk.com

SANY

Quality Changes the World

**SANY HEAVY
MACHINERY (UK) LTD**

info@sanyuk.com
www.sanyuk.com